DAM ON D BARREL BODY LINE



DBL An ideal body for excavation & light demolition work	DBH deal for heavy duty quarry & demolition work
4" x 6" x 3/16" tubing	4" x 6" x 1/4" tubing
4.5 mm (3/16") – HARDOX 450	1/4" – HARDOX 450
NONE	NONE
4.5 mm (3/16") – HARDOX 450	1/4" – HARDOX 450
4.5 mm (3/16") – HARDOX 450	1/4" – HARDOX 450
4.5 mm (3/16") – HARDOX 450	1/4" – HARDOX 450
1/4" — 44-W	1/4" — 44-W
4,948 lbs Based on a 17'6" x 54" x 60" DBL	5,744 lbs Based on a 17'6" x 54" x 60" DBH
13' to 22'	13' to 22'
42" to 66"	42" to 66"
42" to 72"	42" to 72"
88"	88"
Front Mount Telescopic	Front Mount Telescopic

Underbody Hoist

TOP RAIL

SIDES

SIDE POSTS

FRONT

TAILGATE

FLOOR

SILLS

BODY WEIGHT

STANDARD BODY LENGTHS
STANDARD SIDE HEIGHTS
STANDARD TAILGATE HEIGHTS
STANDARD INSIDE WIDTH
STANDARD HOIST SYSTEM

OPTIONAL HOIST SYSTEM

Underbody Hoist

MATERIALS

SPECIFICATIONS