

TRADITIONAL BODY LINE



THE BODIES SHOWN MAY HAVE DEALER INSTALLED OPTIONS.

LTT | The industry standard for weight sensitive versatile work

HTT | The industry standard for the roughest work

TOP RAIL	3" x 4" x 3/16" tubing	3" x 4" x 3/16" tubing
SIDES	1/8" – HARDOX 450	4.5 mm (3/16") – HARDOX 450
SIDE POSTS	10g (0.134") – A-36	10g (0.134") – A-36
FRONT	1/8" – HARDOX 450	4.5 mm (3/16") – HARDOX 450
TAILGATE	4.5 mm (3/16") – HARDOX 450	1/4" – HARDOX 450
FLOOR	4.5 mm (3/16") – HARDOX 450	1/4" – HARDOX 450
SILLS	1/4" – 44-W	1/4" – 44-W
SILLS +	8" or 10" I-Beams – (Optional)	8" or 10" I-Beams – (Optional)
BODY WEIGHT	4,796 lbs Based on a 17' x 48" x 60" LTT	5,867 lbs Based on a 17' x 48" x 60" HTT
STANDARD BODY LENGTHS	10' to 23'	10' to 23'
STANDARD SIDE HEIGHTS	36" to 72"	36" to 72"
STANDARD TAILGATE HEIGHTS	36" to 72"	36" to 72"
STANDARD INSIDE WIDTH	86" to 88" trapezoidal design	86" to 88" trapezoidal design
STANDARD HOIST SYSTEM	Front Mount Telescopic	Front Mount Telescopic
OPTIONAL HOIST SYSTEM	Underbody Hoist	Underbody Hoist

MATERIALS

SPECIFICATIONS